Cabelcon
An Amphenol Company

Datasheet

Item no.	49021200-02

3.5/12M-TL212
Belden Coax 6 SAS PE(Code 49081)

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ohm
	15.0 A @10°C increase
(calculated)	21.2 A @20°C increase

Product photo



Transfer Impedance (CoMeT)	Class A++
	<0.9 mΩ/m @ 5-30MHz
	<0.05 mΩ/item @ 5-30MHz
Screening Attenuation(CoMeT)	Class A++
	>115 dB @ 30-1000MHz
	>115 dB @ 1000-2000MHz
	>105 dB @ 2000-3000MHz

Return Loss (IEC 61169-1)	Better than	Typical
0.3 - 500 MHz	-36 dB	-39.3 dB
500 - 860 MHz	-33 dB	-36.1 dB
860 - 1000 MHz	-32 dB	-35.4 dB
1000 - 1750 MHz	-29 dB	-31.6 dB
1750 - 2150 MHz	-26 dB	-28.6 dB
2150 - 3000 MHz	-22 dB	-26.4 dB

Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-0.06 dB	-0.01 dB
500 - 860 MHz	-0.07 dB	-0.02 dB
860 - 1000 MHz	-0.07 dB	-0.02 dB
1000 - 1750 MHz	-0.08 dB	-0.03 dB
1750 - 2150 MHz	-0.08 dB	-0.03 dB
2150 - 3000 MHz	-0.12 dB	-0.07 dB

Temperature	
Installing	-5° to +50° C
Operating	-40° to +70° C
Storing	-40° to +70° C

Intermodulation	IM3	
3rd Order (@2x+37dBm)	-120 dBc	

Inner Conductor Resistance (@ 1 A DC)	<0.8 mΩ

Sealing Test (IEC IP-code)	IP X8 30 meter / 8 hours

Insulation Resistance (@ 500 VDC)	>200 GΩ

Dielectric Strength DC Test Voltage	>3.0 KV

O-rings	EPDM

Base Material	
Body Parts	Brass CuZn39Pb3
Inner Conductor	Brass CuZn39Pb3

Max. Tensile Strength	
Overall	>309 N
Inner Conductor	>200 N

Plating	
Body Parts	Nitin-6
Inner Conductor	Nitin-6

Torsional Strength (Connector / Cable)	>0.8 Nm

Insulators	COC (Topas) / PP with Glass

Test performed by	Sven-Erik Sandberg
Date of release	July 22, 2015

Remarks

All tests performed using instruments calibrated in accordance to our ISO 9001 certification.
Further technical specifications and installation instructions can be obtained on request.

© Copyright Amphenol Cabelcon ApS
Distributor:

Amphenol Cabelcon ApS

Industriparken 10, DK-4760 Vordingborg
Tel:+45 55985599 Cabelcon@cabelcon.com
www.cabelcon.com